



Dart Aerospace Ltd.
1270 Aberdeen St
Hawkesbury, ON
K6A 1K7
Canada

Tel (613) 632-5200

D3918-1
Job Sheet 169580



Part No: D3918-1

Job Qty: 20 ea

Part Name: Placard



Part Weight: 0 lbs

Status: Scheduled

Priority: Medium

Job Created: 12/14/17

Job Tracking No:

Due Date: 12/21/17

Created By: Chantal Lavoie

Type: Stock

Description:

Customer: L3 Technologies Inc (CL3CO03)

7406 USS Enterprise Street Milton, FL, 32570 USA ph:(850) 981-0087 fx:(850) 981-0089.

Note: DWG REV A

Ship Via:

Bill of Materials

Job Routing

Op No	Operation	Qty	Start Date	Due Date	Standard		Workcenter/Supplier		Sign-off
					Setup hrs	Run Hrs	Workcenter / Supplier	Lead Time	
100	Purchasing	20 pcs		12/21/17	0.00	0.00	Purchasing		SPR-12-28
110	Packaging	20 pcs		12/21/17	0.00	0.00	Packaging2		SPR-12-28
120	QC	20 pcs		12/21/17	0.00	0.00	QC6		38
130	Packaging	20 pcs		12/21/17	0.00	0.00	Packaging3-2	51056	AT 3-89
140	QC21-SA	20 Ea		12/21/17	0.00	0.00	QC21		DEC 14 2017

Job Allocations

Operation	Component Part	Required	Inventory	Allocated	Std Qty
100-Purchasing	D3918-1P	20	0	0	0

Part Specifications

Specifications could not be found.

Plex 12/14/17 7:55 AM dart.lavoie.chantal

DART
AEROSPACE
S027132



Placard


PART NO: D3918-1

Revision:
Operation:
Change No:

Purchasing

Dart Aerospace Ltd.
1270 Aberdeen Street
Hawkesbury, ON K6A 1K7
CANADA
TEL.: 1 613 632-5200
Email: sales@dartaero.com
www.dartaerospace.com

Mfg Date: 12/28/17
Job No: 169580



D3918-1 PLACARD

RELEASED
9/16/08

NOTES:

- 1) MATERIAL: RED LETTERS ON WHITE ADHESIVE BACK VINYL.
MANUFACTURED FROM 3M 7 MIL MASKING FILM #8522CP OR AVERY IPM #2031
SIZE IS 6.25" WIDE X 1.10" HIGH
- 2) FINISH: N/A
- 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
- 4) UNITS: INCHES UNLESS OTHERWISE NOTED
- 5) BREAK SHARP EDGES: N/A
- 6) IDENTIFICATION: N/A
- 7) WEIGHT: N/A

A	NEW ISSUE	PH	09.05.25
REV.	DESCRIPTION	BY	DATE
DESIGN	PH		
DRAWN	PH		
CHECKED			
MFG. APPR.	N/A		
APPROVED			
DE APPR.			
DATE	09.05.25		

DART AEROSPACE LTD
HAWKESBURY, ONTARIO, CANADA

DRAWING NO. REV. A
D3918 SHEET 1 OF 1
TITLE SCALE
PLACARD NTS

COPYRIGHT © 2008 BY DART AEROSPACE LTD
THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS
NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT
WRITTEN PERMISSION FROM DART AEROSPACE LTD



Dart Aerospace Ltd.
1270 Aberdeen St
Hawkesbury, ON
K6A 1K7
Canada

Tel (613) 632-5200

PURCHASE ORDER PO038650

Supplier: STU002-VC
Studio de Lettrage 2001
210 Main West
Hawkesbury
ON
K6A 2H6 Canada
Phone: 613 632 5449
Fax: 613 632 9491

Attention: Grace, Batista

Ship To: 1270 Aberdeen Street
Hawkesbury
ON
K6A 1K7 Canada
Phone: 613-632-5200

PO No: PO038650
PO Date: 12/14/17
Due Date: 12/20/17
**Purchase Order
Revision:**
Revision Date:
Ship-To Contact: Phone:

Via: Ground
Pymt Terms: Net 30
Freight Terms:
Special Comments:

E-MAILED
DEC 15 2017

Items											
Line Item	Part	Supplier Part No	Item No	Description	Status	Due Date	Order Quantity	Received Quantity	Balance	Unit Price (CAD)	Extended Price
1	D3268-1P			Placard As Per Dwg D3268 Rev. A	Firmed	12/20/17	6 pcs	0 pcs	6 pcs	\$13.3333/pcs	\$80.00
2	D3918-1P			Placard As Per Dwg D3918 Rev. A	Firmed	12/20/17	20 pcs	0 pcs	20 pcs	\$2.50/pcs	\$50.00
Grand Total:											\$130.00

DAS
38
9-89

Order Notes

Terms & Condition of Purchasing(Suppliers) and Procurement Quality Clauses are an integral part of our AS9100 requirements. To learn in detail, please visit www.dartaerospace.com for further explanation.

Procurement Quality Clauses
A005 RIGHT OF ENTRY
A007 FIRST ARTICLE INSPECTION (FAI) BY SELLER, (DOCUMENTATION MAINTAINED BY SUPPLIER)
A012 CHEMICAL AND PHYSICAL TEST REPORTS
A016 PERSONNEL QUALIFICATION
A017 RAW MATERIAL IDENTIFICATION (AS APPLICABLE)
A026 CERTIFICATION OF MATERIAL CONFORMANCE
A041 QUALITY MANAGEMENT SYSTEM
A042 DART NOTIFICATION BY SUPPLIER
A043 RETENTION OF QUALITY DOCUMENT

A048 COUNTERFEIT PARTS AVOIDANCE, DETECTION, MITIGATION AND DISPOSITION PROGRAM
A049 SUPPLIER AWARENESS

C. L.
R.B.

Plex 12/14/17 11:26 AM dart.baker.diane

210 Main West
Hawkesbury, Ontario K6A 2H6
Canada

INVOICE

Invoice No.: 45448
Date: 12/20/2017
Ship Date:
Page: 1
Re: Order No.

Sold to:

Dart Aerospace Ltd

1270 Aberdeen
Hawkesbury, Ontario
K6A 1K7

Ship to:

Dart Aerospace Ltd

1270 Aberdeen
Hawkesbury, Ontario
K6A 1K7

Quantity	Description	Base Price	Disc. %	Unit Price	Amount
6	D3268-1P	13.33		13.33	79.98
20	D3918-1P	2.50		2.50	50.00
	PO#038650				
	Attn: Diane B				
	Subtotal:				129.98
	H - HST				16.90
	HST				
SPT 12-28 Thank you for your business / Merci de faire affaire avec nous					
Shipped By:		Tracking Number:		HST: 825007651RT0001	
Comment: WO21670				Total Amount	146.88
				Amount Paid	0.00
Sold By:				Amount Owning	146.88

JAS
38
1-80

******CERTIFICATE of CONFORMITY******

Customer:

Studio SL2

Purchase Order N°:

038650

Packing Slip N°:

Part N°:

Serial N°:

Description:

D3268-1P
D3918-1P

Quantity:

6,20

Certification:

We hereby certify that:

1. The above listed items were manufactured, repaired and/or inspected in accordance with applicable drawings and/or specifications;
2. All work was accomplished in accordance with the Dart Aerospace Purchase Order;
3. Results of all inspections, chemical or physical tests, as well as other evidence, which shows the acceptability of raw materials, parts and/or assembly components are on file and available for inspection at any time.

Authority:

Avery / 1 year shelf life.

APPROVAL:

Valerie Young

DATE:

Signature:

[Handwritten Signature]

Dec 20.17

Title:

office administrator

PRODUCT DATA SHEET



Avery® IPM™ 2031

issued: 01/04/2005

Introduction

Avery® IPM™ 2031 is a high quality pressure-sensitive vinyl film, designed for use on wide format inkjet printers. Avery® IPM™ 2031 has excellent printing properties, allowing crisp print quality with bright and vibrant colours. Avery® IPM™ 2031 offers rapid ink drying and a water-resistant material. It combines good adhesion during its life and easy removal afterwards.

Description

Facefilm: 80-micron premium white calendered, topcoated vinyl.
Adhesive: removable, acrylic based
Backing paper: one side coated kraft paper, 140 g/m²

Features

- Excellent printability
- Vibrant and bright colours
- Crisp print quality
- Spray water resistant with specific pigmented inks
- Good adhesion, excellent removability
- Warranty on outdoor durability

Recommendations for use

A wide variety of full-colour graphics for indoor - and **short/medium term outdoor** applications such as posters, murals, displays, exhibition stands, vehicle graphics etc. Avery® IPM™ 2031 is suitable for application to a wide variety of substrates and will remove cleanly for up to 1 year after application.

IPM media should be handled with care as any surface contamination may affect the print quality. Media should be processed in an environment of 15-25°C and 30-70% relative humidity. After drying, the finished prints should be wrapped in polyethylene film and despatched flat or rolled with the printed side facing outwards. To protect prints against water, UV/light and abrasion, overlamination with a clear film is recommended. For specific details of Avery® DOL combinations, refer to "Technical Bulletin 5.3. Recommended combinations of Avery® Overlaminates and Avery® Digital Print Media"

Always test your combination of Avery® IPM™ medium, inkjet printer and inks prior to commercial use.

Compatibility

Avery® IPM™ 2031 is compatible with a broad selection of inkjet printers, when printing with pigmented, water based inks. For specific details refer to "Technical Bulletin 5.6 Avery Dennison Inkjet Print Media - Printer compatibility".

Durability:

Avery® IPM™ 2031 is warranted for outdoor use in conjunction with pigmented outdoor inks from HP, Encad and Colorspan. The warranted period varies from type of application and type of overlaminate from 18 months up to 5 years. For full details, see our Avery® IPM™ Outdoor warranty.



www.averygraphics.com

Graphics Division
Rijndijk 86, P.O. Box 118
2394 ZG Hazerswoude - The Netherlands
Tel +31 71 3421500 - Fax +31 71 3421538

PRODUCT CHARACTERISTICS

Avery® IPM™ 2031

Physical properties

Features	Test method ¹	Results
Caliper, facefilm	ISO 534	80 µm
Gloss	ISO 2813, 20°	1%
Dimensional stability	DIN 30646	0.3 mm. max
Adhesion, initial	FINAT FTM-1, stainless steel	180 N/m
Adhesion, ultimate	FINAT FTM-1, stainless steel	260 N/m
Flammability		Self extinguishing
Accelerating ageing	DIN 53587, 500h exposure	No negative impact on film Performance
Shelf life	Stored at 22° C/50-55 % RH	2 years
Removability		up to 1 year
Not when applied to: Nitro-cellulose paints, ABS, Polystyrene, certain types of PVC		
Durability ²	Overlaminated with DOL 4300	5 years
	Overlaminated with DOL 1000, DOL 1100 with overlaps	3 years
	Overlaminated without overlaps for static applications only	2 years
	Without overlaminate and used for static, Non-abrasive application ONLY	18 months

Only when printed with ENCAD GO, HP and Colorspan pigmented inks and when properly applied in accordance with our application instructions. Only applicable for vertical exposure.

Temperature range

Features	Results
Application temperature	Minimum: +10°C
Service temperature	-20°C to +80°C

Important

Information on physical and chemical characteristics is based upon tests we believe to be reliable. The values listed herein are typical values and are not for use in specifications. They are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material to their specific use. All technical data are subject to change. In case of any ambiguities or differences between the English and foreign versions of these Conditions, the English version shall be controlling.

Warranty

Avery® branded materials are manufactured under careful quality control and are warranted to be free from defect in material and workmanship. Any material shown to our satisfaction to be defective at the time of sale will be replaced without charge. Our aggregate liability to the purchaser shall in no circumstances exceed the cost of the defective materials supplied. No salesman, representative or agent is authorised to give any guarantee, warranty, or make any representation contrary to the foregoing. All Avery® branded materials are sold subject to the above conditions, being part of our standard conditions of sale, a copy of which is available on request.

1) Test methods

More information about our test methods can be found on our website.

2) Durability

The durability is based on middle European exposure conditions. Actual performance life will depend on substrate preparation, exposure conditions and maintenance of the marking. For instance, in the case of signs facing south; in areas of long high temperature exposure such as southern European countries; in industrially polluted areas or high altitudes, exterior performance will be decreased.



www.averygraphics.com

Graphics Division

Rijndijk 86, P.O. Box 118
2394 ZG Hazerswoude - The Netherlands
Tel +31 71 3421500 - Fax +31 71 3421538